

## Adhesive Properties - Substrate Matching Chart

Adhesives	Description	VPI Products to be Adhered	Application (Where to Use)	Substrate	Trowel	Approx Coverage	Foot Traffic Dry Time	VOC gm/l	MVER Max Level	RH% Max	pH
<b>VPI 150</b>	Solvent Free 2 Part Conductive Epoxy Adhesive	ESD Static Control Tile	Superior bond strength, on grade, above grade, below grade and applications where moisture may be a concern.	Porous Non - Porous	1/16" x 1/16" Square Notch with 1/16" flats	Nominally 135 Sq. Ft. per gallon	24 Hours	Zero	5 LBS.	85%	6 - 9
<b>VPI 165</b>	Solvent Free 1 Part Conductive Acrylic Adhesive	ESD Static Control Tile	On Grade or Above Grade <b>(Not for below grade)</b>	Porous Non - Porous	1/16" x 1/16" Square Notch with 1/16" flats	Nominally 135 Sq. Ft. per gallon	24 Hours	Zero	5 LBS.	85%	7 - 11
<b>VPI 100</b>	Solvent Free 2 Part Epoxy Adhesive	(PRT) Premium Resilient Tile, Rubber Tile, Treads, Risers, Stringers	Superior bond strength, on grade, above grade, below grade and applications where moisture may be a concern.	Porous Non - Porous	1/16" x 1/16" Square Notch with 1/16" flats	Nominally 135 Sq. Ft. per gallon	24 Hours	Zero	5 LBS.	85%	6 - 9
<b>VPI 190</b>	Solvent Free 1 Part Contact Adhesive	Accessories / Transitions	Superior tack and bond strength, on grade, above grade	Porous Non - Porous	n/a	Nominally 300 Sq. Ft. per gallon	24 Hours	Zero	n/a	n/a	10 - 12
<b>VPI 520</b>	Solvent Free 1 Part Pressure Sensitive Adhesive	(PRT) Premium Resilient Tile,	On Grade or Above Grade <b>(Not for below grade)</b>	Porous Non - Porous	1/16" x 1/16" Square Notch with 1/16" flats	Nominally 135 Sq. Ft. per gallon	24 Hours	Zero	5 LBS.	85%	7 - 11
<b>VPI 560</b>	Vinyl Acrylic 1 Part Adhesive	Rubber Tile <b>(Not Treads, Risers or Stringers)</b>	On Grade or Above Grade <b>(Not for below grade)</b>	<u>Porous</u> <u>Non - Porous</u>	1/16" x 1/16" Square Notch with 1/16" flats	Nominally 135 Sq. Ft. per gallon	24 Hours	Zero	5 LBS.	0.8	7 - 9
<b>VPI 600</b>	Solvent Free 1 Part Latex Acrylic Adhesive	Vinyl & Rubber Wall Base	Above Grade <b>(Not for below grade)</b>	<u>Porous Only</u>	Not required if using cartridge tubes or 1/16" x 1/16" Square Notch with 1/16" flats	Nominally 275 Ln. Ft. per gallon	N/A	Zero	N/A	N/A	N/A
<b>VPI NC-2 Nose Caulking</b>	Solvent Free 2 Part Epoxy Filler Caulk 400 ml cartridge / tube	Stair Tread Nosing	All applications	Porous Non - Porous	None	35 - 50 Lin. Ft. @ 1/4" bead per cartridge / tube	N/A	13	N/A	N/A	N/A

**NOTE: Actual coverage will vary and depending on the substrate conditions, porosity, substrate and atmospheric temperature, humidity, application methodology and many other variables. If more adhesive is required, please purchase from your local distributor.**

**VPI Technical Service: (800) 874-4240**

